# **SAFETY DATA SHEET**



BG Frigi-Fresh® - Fragrance Free

# 1. Product and company identification

Manufacturer	: BG Products Inc. 701 S. Wichita Street Wichita, KS, 67213, USA www.bgprod.com
Relevant identified uses of	of the substance or mixture and uses advised against
MSDS #	: 707
Validation date	: 1/27/2015.
Responsible name	: Kolin Anglin, Environmental Coordinator 316-265-2686 msds@bgprod.com
In case of emergency	: (800) 424-9300 (CHEMTREC)

# 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).			
Classification of the substance or mixture	<ul> <li>FLAMMABLE AEROSOLS - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3</li> </ul>			
GHS label elements	Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 33.8%			
Hazard pictograms				
Signal word	: Danger			
Hazard statements	: Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness and dizziness.			
Precautionary statements				
Prevention	: Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Wash hands thoroughly after handling.			
Response	: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.			
Storage	: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.			
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.			
Hazards not otherwise classified	: None known.			

# 3. Composition/information on ingredients

Substance/mixture	1	Mixture
Other means of	5	Not available.
identification		
CAS number/other identifiers		
CAS number	1	Not applicable.
Product code	÷	707
Ingredient name		
Isopropyl alcohol 2,2'-(ethylenedioxy)diethanol		

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

%

40 - 70

5 - 10

**CAS** number

67-63-0

112-27-6

### 4. First aid measures

Description of necessary first	aid measures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Most important symptoms/eff	-
Potential acute health effects	<u>5</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: Can cause central nervous system (CNS) depression. Irritating to mouth, throat and stomach.

**Over-exposure signs/symptoms** 

### 4. First aid measures

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
See toxicological information	on (Section 11)

### 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

### 6. Accidental release measures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# 7. Handling and storage

Precautions for safe handling	L	
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

# 8. Exposure controls/personal protection

#### **Control parameters**

#### **Occupational exposure limits**

Ingredient name	Exposure limits		
Isopropyl alcohol	ACGIH TLV (United States, 6/2013). TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes. OSHA PEL 1989 (United States, 3/1989). TWA: 400 ppm 8 hours. TWA: 980 mg/m <sup>3</sup> 8 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m <sup>3</sup> 15 minutes. NIOSH REL (United States, 4/2013). TWA: 400 ppm 10 hours. TWA: 980 mg/m <sup>3</sup> 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m <sup>3</sup> 15 minutes. STEL: 1225 mg/m <sup>3</sup> 15 minutes. STEL: 1225 mg/m <sup>3</sup> 15 minutes. TWA: 980 mg/m <sup>3</sup> 15 minutes. TWA: 400 ppm 8 hours. TWA: 400 ppm 8 hours. TWA: 400 ppm 8 hours. TWA: 980 mg/m <sup>3</sup> 8 hours.		
Appropriate engineering controls	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.		
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
Individual protection measured	<u>res</u>		
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.		
Skin protection			
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.		
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.		
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		
Date of issue/Date of revision	: 1/27/2015. Date of previous issue : 4/26/2010. Version : 1 5/1		

### 8. Exposure controls/personal protection

**Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

### 9. Physical and chemical properties

Physical state	: Liquid. [Aerosol.]
Flash point	: Not available.
Auto-ignition temperature	: Not available.
Flammable limits	: Not available.
Color	: Clear.
Odor	: Odorless.
рН	: Not available.
<b>Boiling/condensation point</b>	: Not available.
Melting/freezing point	: Not available.
Specific gravity	: 0.91
Vapor pressure	: Not available.
Vapor density	: >1 [Air = 1]
Odor threshold	: Not available.
Evaporation rate	: Not available.
Solubility	: Easily soluble in the following materials: cold water and hot water.
Density	: 7.589 (lbs/gal)
Aerosol product	
Type of aerosol	: Spray
Heat of combustion	: 1.422 kJ/g

### 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Isopropyl alcohol	LD50 Dermal LD50 Oral		12800 mg/kg 5000 mg/kg	-
2,2'-(ethylenedioxy)diethanol	LD50 Oral		15000 mg/kg	-

Irritation/Corrosion

### Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Isopropyl alcohol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	10 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100	-
				milligrams	
	Skin - Mild irritant	Rabbit	-	500	-
				milligrams	
2,2'-(ethylenedioxy)diethanol	Eyes - Mild irritant	Rabbit	-	500	-
				milligrams	
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				milligrams	

#### **Sensitization**

Not available.

#### **Mutagenicity**

Not available.

#### **Carcinogenicity**

Not available.

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Isopropyl alcohol	-	3	-

#### **Reproductive toxicity**

Not available.

#### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Isopropyl alcohol	Category 3	Not applicable.	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

#### Aspiration hazard

Not available.

#### Information on the likely : Not available. routes of exposure

#### Potential acute health effects

1	Causes serious eye irritation.	
1	Can cause central nervous system (CNS) depression. dizziness.	May cause drowsiness and
1	No known significant effects or critical hazards.	
1	Can cause central nervous system (CNS) depression. stomach.	Irritating to mouth, throat and
	:	<ul><li>No known significant effects or critical hazards.</li><li>Can cause central nervous system (CNS) depression.</li></ul>

Symptoms related to the physical, chemical and toxicological characteristics

# Section 11. Toxicological information

		0		
Eye contact	-	Adverse symptoms may include the following: pain or irritation watering redness		
Inhalation	:	Adverse symptoms may include the following: respiratory tract irritation coughing nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness		
Skin contact	:	No specific data.		
Ingestion	:	No specific data.		
Delayed and immediate effect	ts	and also chronic effects from short and	<u>d long term exposure</u>	
<u>Short term exposure</u>				
Potential immediate effects	:	Not available.		
Potential delayed effects	:	Not available.	Not available.	
Long term exposure Potential immediate effects	:	Not available.		
Potential delayed effects	:	Not available.		
Potential chronic health effe Not available.	<u>ect</u>	<u>S</u>		
General	:	No known significant effects or critical ha	azards.	
Carcinogenicity	:	No known significant effects or critical ha	azards.	
Mutagenicity	:	No known significant effects or critical ha	azards.	
Teratogenicity	:	No known significant effects or critical hazards.		
Developmental effects	:	No known significant effects or critical hazards.		
Fertility effects	:	No known significant effects or critical hazards.		
Numerical measures of toxic	ity			
Acute toxicity estimates				
Route			ATE value	

Oral

5516.7 mg/kg

# 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Isopropyl alcohol	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 1400000 µg/l	Fish - Gambusia affinis	96 hours
2,2'-(ethylenedioxy)diethanol	Acute LC50 35000 ul/L Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 10000000 µg/l Marine water	Fish - Menidia beryllina	96 hours
	Chronic NOEC 7500 mg/l Fresh water	Daphnia - Daphnia magna	21 days
	Chronic NOEC 100 ul/L Marine water	Fish - Cyprinodon variegatus -	28 days
		Egg	

Persistence and degradability

Not available.

### 12. Ecological information

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Isopropyl alcohol	0.05	-	low
2,2'-(ethylenedioxy)diethanol	-1.75		low

#### Mobility in soil

Soil/water partition : Not available.

coefficient (K<sub>oc</sub>) Other adverse effects

: No known significant effects or critical hazards.

### 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

# 14. Transport information

	DOT Classification	IMDG	ΙΑΤΑ
UN number	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS, flammable	AEROSOLS, flammable	AEROSOLS, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	<u>Limited quantity</u> Yes.	Emergency schedules (EmS) F-D, S-U <u>Remarks</u> Limited quantity	Passenger and CargoAircraftAircraftQuantity limitation: 75kgCargo Aircraft OnlyQuantitylimitation: 150 kgLimited Quantities -Passenger AircraftQuantitylimitation: 30 kgRemarksLimited quantity

### 14. Transport information

Special precautions for user	: <b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
Transport in bulk according to Annex II of MARPOL	: Not available.

73/78 and the IBC Code

### 15. Regulatory information

U.S. Federal regulations

: TSCA 8(a) CDR Exempt/Partial exemption: Not determined United States inventory (TSCA 8b): All components are listed or exempted.

#### SARA 302/304

Composition	information on	<b>ingredients</b>

No products were found.

SARA 304 RQ : Not applicable.

#### SARA 311/312

Classification

: Immediate (acute) health hazard Delayed (chronic) health hazard

#### Composition/information on ingredients

Name		Sudden release of pressure		Immediate (acute) health hazard	Delayed (chronic) health hazard
Isopropyl alcohol	Yes.	No.	No.	Yes.	Yes.

#### **SARA 313**

	Product name	CAS number
Form R - Reporting requirements	Isopropyl alcohol	67-63-0
Supplier notification	Isopropyl alcohol	67-63-0

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations

Massachusetts	: The following components are listed: ISOPROPYL ALCOHOL
New York	: None of the components are listed.
New Jersey	: The following components are listed: ISOPROPYL ALCOHOL; 2-PROPANOL
Pennsylvania	<ul> <li>The following components are listed: 2-PROPANOL; ETHANOL, 2,2'-[1, 2-ETHANEDIYLBIS(OXY)]BIS-</li> </ul>
United States inventory (TSCA 8b)	: All components are listed or exempted.
<u>Canada</u>	
WHMIS (Canada)	: Class B-5: Flammable aerosol. Class D-2B: Material causing other toxic effects (Toxic).
<u>Canadian lists</u>	
Canadian NPRI	: The following components are listed: Isopropyl alcohol
<b>CEPA</b> Toxic substances	: None of the components are listed.
Canada inventory	: All components are listed or exempted.

 Date of issue/Date of revision
 : 1/27/2015.
 Date of previous issue
 : 4/26/2010.
 Version
 : 1

### 15. Regulatory information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations	
International lists	: Australia inventory (AICS): All components are listed or exempted.
	China inventory (IECSC): All components are listed or exempted.
	Japan inventory: Not determined.
	Korea inventory: All components are listed or exempted.
	Malaysia Inventory (EHS Register): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.
	Philippines inventory (PICCS): All components are listed or exempted.
	Taiwan inventory (CSNN): Not determined.

### 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

<u>History</u>	
Date of printing	: 1/27/2015.
Date of issue/Date of revision	: 1/27/2015.
Date of previous issue	: 4/26/2010.
Version	: 1

### **16.** Other information

Key to abbreviations	: ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,
	1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	UN = United Nations
References	: Not available.

Indicates information that has changed from previously issued version.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.